



Mr. Grande

SMART EXTERIOR COLOURLESS PRIMER

DESCRIPTION:

I'm Mr. Grande. I offer you the most luxurious paint finish for your interiors. There could be no better choice than me as I have the best combination of Smart Technologies to provide an exquisite finish for your walls like no other paint can.

KEY FEATURES :



Smart Clean

Quartz Paint technology forms a Quartz shield that develops a repellent nature for the surface of the substrate that does not allow water to get in to the wall itself as it's rendered hydrophobic which leads to a waterproof surface.



Perfect Finish

Our paint is also formulated to form thick layers of coating which do not thin over time like conventional paints do in the market due to wear and tear, wind erosion and pollution. And thus, our paint is not only smart but perfect finish.



FadeProof

Fade Proof and Smart Cool technology does not allow excessive UV Radiation and weathering to cause chalking of the paint on the wall, which ultimately causes fading.



Anti Efflorescence

Smart Quartz Shield and Smart Hydrophobic Technology stops the migration of lime water molecules (Ca(OH)_2) which are the reason behind the formation of the crystalline deposits of soluble salts causing Efflorescence on the walls.



Fire Resistant

Fire Resistant technology helps to stop the fire from spreading in case of fire. It reduces flammability and combustion of building materials it coats. While it does not prevent fires from occurring, but delays the expansion of fires.



Anti Allergy

Quartz Paint technology and Smart Hydrophobic Technology stops any types of elements and germs which will convert into allergies and our paint not only protects walls but anyone who resides inside.



Crack Proof

Hydrophobic technology and Smart Breathing feature avoids penetration of high levels of moisture in the wall, which can cause flaking, peeling or cracking of the walls in future.



Anti Virus

Quartz Paint technology and Smart Hydrophobic technology stops any type of Viruses from sticking to the walls and thus the paint does not foster their growth.



Anti Bacteria

Anti Bacteria and Quartz Paint technology feature avoids the growth of any type of bacteria as penetration of high levels of moisture in the wall is not allowed.



Low VOC (Volatile Organic Compounds)

Our paint consists of low Volatile Organic Compounds which is eco-friendly and good for the health of people who reside inside the structure.



Odorless

Our Paint technology avoids dampness, growth of mould and algae, surfactant leaching, efflorescence and many other problems which can release weird odor in the environment. Thus our paints and coatings are odorless.

COVERAGE :

On normal masonry surface after brushing/roller

1 COAT 270 – 310 sq.ft/ltr**

2 COAT 140 – 160 sq.ft/ltr**

(**Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.)

POST APPLICATION CARE :

- The Golden rule for removing any wall stains is that one should remove it immediately.
- Remove all dirt using a clean cloth or duster. Always remove dirt from top to bottom, this helps in avoiding loose dirt to smudge the walls.
- For regular household stains like pencil, tea, coffee, crayons etc, use 5% soap/detergent solution. Use a sponge to remove the stains.
- In case of tough stains like turmeric, sketch pen, use a mild detergent solution for cleaning the stains.

APPLICATION METHOD :

PLASTER : New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING : Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Mr Smooth to limit further dampness.

FILLING FOR CRACKS : For filling cracks up to 3mm use Mr. Crackheal.

FILLING FOR HOLES & DENTS : In case of dents and holes use Mr. Super Acrylic Wall Putty or white cement and fine sand in the ratio 1:3

For interior surfaces or substrates that are subjected to continuous seepage or dampness, kindly use Mr. Smooth before the top coat application. Best applied diluted by (30-40% water) low-pressure spray (not airless) or roller with surface temperature between 10 degree Celsius and 40 degree Celsius.

COLOURS AVAILABLE : -1560 COLOURS

PRECAUTIONS :

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not over-thin or over-extend the brush.
- Tint using Skora Paints machine colorants only
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.

HEALTH & SAFETY

If contact with eyes use water to wash.

AREAS OF USE:

Caste-in-place concrete	Yes
Pre caste concrete	Yes
Cement Stucco / Plaster	Yes
Skim Coat	Yes
Brickwork	No
Blockwork	No
Fibre cement sheet	Yes
Stone	No

PRODUCT DATA :

Drying time	Surface dry time 30 min
Sheen levels	8 - 14 at 60 deg GH
Stability of thinned paint	To be used within 24 hours

SAFETY FEATURES :

Store the container with the lid tightly closed in an upright position, in a cool, dry place.

Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion seek immediate medical attention.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

In the event of spills, contain spillage using sand or earth.

No added Lead, Mercury or Chromium compounds.

PACKAGING :

4 Liter, 20 Liter

Note : The information provided is intended as a guide only and is correct to best of our knowledge at time of issue. It should not be considered as a definite approval for suitability for a particular purpose.



Updated on : 10/10/2020. Please note that this data sheet supersedes all previous versions.

SKORA COATINGS

Plot No. H-15, M.I.D.C., Satara, Pin Code 415004 | Consumer Relations Manager Tel. 02162 - 244310

Email: reachout@skoracoatings.com | Web: www.skorapaints.com